

**BEST AVAILABLE COPY**

## 1. Notes:

- Requested in para. 4, applicants apologize, but they do not possess a full copy of JP Hei 3-85886 translation.
- Required in para. 5, corrected drawing sheets were submitted on Nov. 4, 2003, and are shown in PAIR under the entry of: Nov. 10, 2003 Drawings.
- Para. 8 asserted the cited art deemed proper because no certified translation was submitted. Applicants respectfully note a certified translation was submitted on May 5, 2004, and is shown in PAIR under the entry May 5, 2004 Foreign Priority Papers Filed.
- From the Office Action, pg. 6, applicants confirm that the test method in itself is not a structural element. The test method simply provides a context for construing the structural limitation "a ventilation resistance value in a horizontal direction that does not exceed 0.20 Kpa·s/m"

## 2. Claims 3, 7, 10, 16 and 20 have been amended to remove the term "configured."

3. On attached sheets, applicants provide an amended claim 1, incorporating the limitations of claim 11, and an amended claim 11, incorporating the limitations of claim 12. Applicants also clarify claim 21. In the interview, applicants would like to discuss these three claims, as provided in two comments below.




4. Amended claim 11 (old claim 12) (and dependent claims): the notched "terminal portion" described in the specification is not an "open edge" (page 7 Office Action), but rather is at the end of each aperture in contact with the absorption sheet. The notching improves airflow from the aperture into the cavity under the surface sheet, and thus provides substantial horizontal breathability, as is discussed in specification. The cited art clearly does not show such a notched terminal portion.

5. Amended claim 1 (similar to old claim 11), amended claim 11, and amended claim 21: The rejections of claims 1-21 were based on inherence. Inherence requires that the asserted feature necessarily be present. See:

M.P.E.P. 2112 IV. ... "The fact that a certain result or characteristic may occur or be present in the prior art is not sufficient to establish the inherency of that result or characteristic." ... "To establish inherency, the extrinsic evidence 'must make clear that the missing descriptive matter is necessarily present in the thing described in the reference, and that it would be so recognized by persons of ordinary skill. Inherency, however, may not be established by probabilities or possibilities. The mere fact that a certain thing may result from a given set of circumstances is not sufficient." ... "In relying upon the theory of inherency, the examiner must provide a basis in fact and/or technical reasoning to reasonably support the determination that the allegedly inherent characteristic necessarily flows from the teachings of the applied prior art."

The asserted characteristic is not necessarily present in the cited art. More particularly, possible configurations of the device described in JP-A-H03-85886 could lack a cavity providing horizontal breathability, so that feature is not inherent under M.P.E.P. 2112. For example, claim 2 of the cited reference reads upon a hypothetical tray mat, as depicted on the next page. That tray mat fails to have a cavity providing horizontal breathability. Therefore that feature is not inherent.

Thanks for considering these positions of the applicants.



**Amendments to the Claims;**

This listing of claims will replace all prior versions, and listings, of claims in the application.

**Listing of Claims;**

1. (currently amended) A drip absorption mat to be laid under a drip-oozing food comprising:
  - an absorption sheet configured to absorb drips; and
  - a porous surface sheet adjoining the absorption sheet, and having a first side facing said absorption sheet and a second side configured to adjoin the food;
    - wherein said porous surface sheet comprises a film having a plurality of protrusions, each protrusion having a convex side and a concave side;
    - wherein a hollow cavity is formed adjacent the protrusions on the convex side;
    - wherein a pore is provided at the bottom of said concave side of each protrusion such that the protrusion forms a minute aperture; and
    - ~~wherein said porous surface sheet is configured to prevent color deterioration on a side of the food adjoining said porous surface sheet by adding adds~~ to the breathability of said absorption sheet in both the horizontal and thickness directions.
2. (previously presented) A drip absorption mat according to Claim 1;
  - wherein said absorption sheet comprises a non-woven fabric having a thickness in the range of 0.3 mm to 3.0 mm.
3. (currently amended) A drip absorption mat, for use with a tray configured with a mounting surface on which the food is to be placed, according to Claim 1;
  - ~~wherein said drip absorption mat is configured as a tray mat sized~~ to be laid on the mounting surface of the tray between the tray and the food.

4. (previously presented) A drip absorption mat to be laid under a drip-oozing food comprising:

an absorption sheet configured to absorb drips; and

a porous surface sheet adjoining the absorption sheet, and having a first side facing the absorption sheet and a second side configured to adjoin the food;

wherein the drip absorption mat is characterized by a ventilation resistance, in the thickness direction, that does not exceed 1.00 Kpa·s/m.

5. (previously presented) A drip absorption mat according to Claim 4;

wherein a ventilation resistance value of said porous surface sheet in the thickness direction does not exceed 0.20 Kpa·s/m.

6. (previously presented) A drip absorption mat according to Claim 4;

wherein said absorption sheet comprises a non-woven fabric having a thickness in the range of 0.3 mm to 3.0 mm.

7. (currently amended) A drip absorption mat, for use with a tray configured with a mounting surface on which the food is to be placed, according to Claim 4;

wherein said drip absorption mat is ~~configured as a tray mat sized~~ to be laid on the mounting surface of the tray between the tray and the food.

8. (previously presented) A drip absorption mat according to Claim 4;

wherein said drip absorption mat is characterized by a ventilation resistance value in a horizontal direction that does not exceed 0.20 Kpa·s/m when measured by a test methodology, comprising:

laying a plurality of drip absorption mats one on top of another to build a drip absorption mat stack;

excising a cylinder of 28 mm in diameter and 5.0 mm thick in the direction of layering;

and

aerating said cylindrically excised drip absorption mat stack in the horizontal direction.

9. (previously presented) A drip absorption mat according to Claim 8;  
wherein said absorption sheet comprises a non-woven fabric having a thickness in the range of 0.3 mm to 3.0 mm.

10. (currently amended) A drip absorption mat, for use with a tray configured with a mounting surface on which the food is to be placed, according to Claim 8;  
wherein said drip absorption mat is ~~configured as a tray mat sized~~ to be laid on the mounting surface of the tray between the tray and the food.

11. (currently amended) A drip absorption mat to be laid under a drip-oozing food comprising:  
an absorption sheet configured to absorb drips; and  
a porous surface sheet adjoining the absorption sheet, and having a first side facing the absorption sheet and a second side configured to adjoin the food;  
wherein said porous surface sheet comprises a film having a plurality of protrusions, each protrusion having a convex side and a concave side;  
wherein a hollow cavity is formed adjacent the ~~protrusion~~ protrusions on the convex side;  
and  
wherein a pore is provided at the bottom of said concave side of each protrusion such that the protrusion forms a minute aperture;  
wherein a terminal portion of said porous surface sheet is in contact with the absorption sheet; and  
wherein the terminal portion is notched so as to facilitate air flow between the hollow cavities and the apertures.

12. (canceled)

13. (previously presented) A drip absorption mat according to Claim 11;  
wherein said minute aperture is tapered with an opening of larger diameter on a side configured to adjoin the food.

14. (previously presented) A drip absorption mat according to Claim 11;  
wherein said absorption sheet and said porous surface sheet are adhered to each other in a manner that does not clog said minute aperture.

15. (previously presented) A drip absorption mat according to Claim 14;  
wherein the absorption and porous surface sheets are glued either at dots or in a line.

16. (currently amended) A drip absorption mat, for use with a tray configured with a mounting surface on which the food is to be placed, according to Claim 15;  
wherein said drip absorption mat is ~~configured as a tray mat sized~~ to be laid on the mounting surface of the tray between the tray and the food.

17. (previously presented) A drip absorption mat according to Claim 11;  
wherein said surface sheet defines a space occupied as a whole, said film occupying not more than 30% of the space occupied as a whole.

18. (original) A drip absorption mat according to Claim 11;  
wherein the number of said apertures is not below 20 per 1 cm<sup>2</sup>.

19. (previously presented) A drip absorption mat according to Claim 11;  
wherein said drip absorption mat is characterized by a ventilation resistance value in a horizontal direction that does not exceed 0.20 Kpa's/m when measured by a test methodology, comprising:  
laying a plurality of drip absorption mats one on top of another to build a drip absorption mat stack;  
excising a cylinder of 28 mm in diameter and 5.0 mm thick in the direction of layering;  
and  
aerating said cylindrically excised drip absorption mat stack in the horizontal direction.

20. (currently amended) A drip absorption mat, for use with a tray configured with a mounting surface on which the food is to be placed, according to Claim 11;  
wherein said drip absorption mat is ~~configured as a tray mat sized~~ to be laid on the mounting surface of the tray between the tray and the food.

21. (previously presented) An absorption mat for receiving food item oozing liquid, comprising:

an absorption sheet configured to absorb liquid; and

a porous surface sheet adjoining the absorption sheet, and having a first side facing the absorption sheet and a second side for adjoining the food item, the first side defining a cavity between the absorption sheet and the surface sheet;

wherein the surface sheet is configured to support the food item while maintaining the cavity between the absorption sheet and the surface sheet; and

wherein the surface sheet defines pores that allow liquid from the food item to flow through to the absorption sheet; and

wherein the cavity adds horizontal breathability to the absorption mat.

**Employee Locator**  
query by name**RECEIVED**  
**CENTRAL FAX CENTER**

SEP 09 2004

<b>Name</b> CHANG VICTOR S								
<b>Employee No</b> 78796								
<b>Organization</b> P/1771 -- GROUP ART UNIT 1771								
<b>Email</b> victor.chang@uspto.gov								
<b>System Login Id</b> vchang1								
<b>Primary</b>	<b>Bldg</b>	<b>Floor</b>	<b>Suite</b>	<b>Corr.</b>	<b>Room</b>	<b>Zone</b>	<b>Planned Move</b>	<b>Status</b>
*	REM	06		A	40			Current
<b>CONTACT NUMBER</b>								
<b>Primary</b>	<b>Type</b>		<b>Number</b>			<b>Ext</b>	<b>Planned Move</b>	<b>Status</b>
*	Telephone		(571)272-1474					Current

**Enter the Employee's Name as follows:**

- Only the **first few letters** of the Last Name **or**,
- Complete **Last Name** followed by a **SPACE** and at least the first few **letters** of the First Name.

Name:

**Employee Locator**  
query by name**RECEIVED**  
**CENTRAL FAX CENTER**

SEP 09 2004

Name <b>MORRIS TERELL (TERREL) H</b>								
Employee No <b>69336</b>								
Organization <b>P/1771 -- GROUP ART UNIT 1771</b>								
Email <b><u>terrel.morris@uspto.gov</u></b>								
System Login Id <b>tmorris1</b>								
<b>Primary</b>	<b>Bldg</b>	<b>Floor</b>	<b>Suite</b>	<b>Corr.</b>	<b>Room</b>	<b>Zone</b>	<b>Planned Move</b>	<b>Status</b>
<b>*</b>	<b>REM</b>	<b>06</b>		<b>A</b>	<b>81</b>			<b>Current</b>
<b>CONTACT NUMBER</b>								
<b>Primary</b>	<b>Type</b>		<b>Number</b>			<b>Ext</b>	<b>Planned Move</b>	<b>Status</b>
<b>*</b>	<b>Telephone</b>		<b>(571)272-1478</b>					<b>Current</b>

**Enter the Employee's Name as follows:**

- Only the **first few letters** of the Last Name **or**,
- Complete **Last Name** followed by a **SPACE** and at least the first few **letters** of the First Name.

Name:

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**